ISOLENA

Technical data sheet

PREMIUM 20kg/m³







Sheep's wool insulation ISOLENA Premium 20kg/m³ with biocide-free wool protection lonic Protect® made from 100% pure sheep's wool without synthetic additives or supporting fibres. The insulating material is renewable, durable, reusable, fully recyclable and certified with the NaturePlus eco-label.

Form of delivery

Article variants according to price list, special dimensions and formats on request.

Thickness mm	Width mm	Length mm
160	600	3 000
180	600	2 500
200	600	2 500
240	600	2 000
260	600	2 000
280	600	2 000
300	600	2 000



C€ CE-003/PRE/2020-01-15



Applications

Thermal insulation: Ceiling - not accessible, Top floor ceiling, tie-beam roof, External wall, Facade insulation, Roof insulation, Between rafter insulation, Rafter insulation

Technical data: Product

Property	Value	Unit of measurement	Standard
Mould growth intensity	0		EAD 040005-00-1201 Annex B
Eco-label NaturePlus	0103-1006-099-1		
Length-related flow resistance kPa s/m²	4,1	kPa s/m²	EN 29053-1
Thermal conductivity	0,035	tr W/mK	
Resistance to insect pests	Klasse 0		EAD 040005-00-1201, Annex C
Vapour diffusion resistance factor µ	1	μ	EN ISO 12572
Water absorption during short-term, partial immersion WS	0,98-2,45	kg/m²	EN 1609
Specific heat capacity c	1760	J/kg K	
European technical approval	ETA-07/0214		
Water absorption during long-term, partial immersion WL(P)	0,98-2,45	kg/m²	EN ISO 16535
Borates toxic to reproduction: None			DIN EN 16516
Fire behavior	D-s2, d0, RF3		SN EN 13501-1

Ecological indicators

All ecological indicators according to EN-15804 such as GWP total, GWP biogenic, PENRT etc. can be found in the Environmental Product Declaration (EPD).

Useful additional documents such as tender texts, links to building material databases etc. can be found in compact form in the download area of our website *Test certificates upon request*.